



ダイキンエアコン

新冷媒(R410A)シリーズ
空冷ヒートポンプエアコン
《レバノール形》

取扱説明書

●この取扱説明書には、工事用ヒーターの使用の合理化に関する法律に基づき経済産業省告示213号(平成21年)による表示事項を記載しております。(冷房専用形は別表外です。)

■EcoZ(EAS800)の性能について

室外ユニット	室内ユニット	冷暖能力	冷暖能力	消費電力	消費電力	運転エネルギー消費効率	区分名
形式	台数	(kW)	(kW)	(kW)	(kW)	(A/F)	
RZ2P780BA形	HHQ780BA	1	7.1	8.0	1.81	1.80	8b
	HHQ780A	2	7.1	8.0	1.61	1.60	8b
	HHQ780A	2	7.1	8.0	2.06	2.05	8b
	HHQ780A	2	7.1	8.0	2.06	2.05	8b
	FAP780A	2	7.1	8.0	1.78	1.77	8b
	FAP780A	2	7.1	8.0	2.18	2.17	8b
	FAP780A	2	7.1	8.0	2.03	2.02	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
	FAP780A	2	7.1	8.0	2.05	2.04	8b
RZ2P112BA形	HHQ112BA	1	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.35	2.34	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
	HHQ112BA	2	10.0	11.2	2.51	2.51	8c
RZ2P140BA形	HHQ140BA	1	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c
	HHQ140BA	2	12.5	14.0	3.48	3.48	8c

室外ユニット	室内ユニット	冷暖能力	冷暖能力	消費電力	消費電力	運転エネルギー消費効率	区分名
形式	台数	(kW)	(kW)	(kW)	(kW)	(A/F)	
RZ2P780BA形	HHQ780BA	1	14.0	16.0	4.67	3.52	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
	HHQ780BA	2	14.0	16.0	3.83	3.55	8c
RZ2P112BA形	HHQ112BA	1	20.0	22.4	7.06	5.41	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
	HHQ112BA	2	20.0	22.4	5.85	5.40	8c
RZ2P140BA形	HHQ140BA	1	24.0	27.2	9.59	7.02	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c
	HHQ140BA	2	24.0	27.2	7.00	6.55	8c

★1/1で示された数値は左が50℃、右が60℃です。その他は50℃、90℃は適です。

室外ユニット	室内ユニット	冷暖能力	冷暖能力	消費電力	消費電力	運転エネルギー消費効率	区分名
形式	台数	(kW)	(kW)	(kW)	(kW)	(A/F)	
RZ2P780BA形	HHQ780BA	1	25.0	28.0	9.95	7.98	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
	HHQ780BA	2	25.0	28.0	7.98	7.20	8d
RZ2P112BA形	HHQ112BA	1	30.0	34.0	10.9	8.40	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
	HHQ112BA	2	30.0	34.0	8.40	7.20	8d
RZ2P140BA形	HHQ140BA	1	35.0	40.0	12.9	9.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d
	HHQ140BA	2	35.0	40.0	9.40	8.40	8d

●省エネ基準について

室内ユニット	冷暖能力	運転エネルギー消費効率(AFP)	区分名
形式	(kW)		
HHP~形 HHP~形 HHP~形	3.6	6.0	8d
	4.0	5.9	
	4.5	5.8	
	5.0	5.7	
	5.5	5.6	
	6.0	5.5	
	6.5	5.4	
	7.0	5.3	
	7.5	5.2	
	8.0	5.1	
	8.5	5.0	
	9.0	4.9	
	9.5	4.8	
	10.0	4.7	
	10.5	4.6	
	11.0	4.5	
上記以外	11.5	4.4	8d
	12.0	4.3	
	12.5	4.2	
	13.0	4.1	
	13.5	4.0	
	14.0	3.9	
	14.5	3.8	
	15.0	3.7	
	15.5	3.6	



ダイキンエアコン

新冷媒(R410A)シリーズ
空冷ヒートポンプエアコン
《レバノート形》

取扱説明書

●この取扱説明書には、ヒートポンプの使用の合理化に関する方法に基づき経済産業省告示213号(平成21年)による省エネルギー表示を記載しております。(冷房専用形は別表外です。)

■ZEASシリーズの性能について

室外ユニット	形式	室内ユニット	台数	冷房能力 (kW)	暖房能力 (kW)	冷房 消費電力 (kW)	暖房 消費電力 (kW)	省エネ率 消費効率 (APF)	区分名
R2YPT12BA形	FHQ122AL	FHO122AL	1	10.0	11.2	2.83	2.67	5.2	ac
		FHP122AL	2	10.0	11.2	2.68	2.65	5.2	ac
		FHP122AL	2	10.0	11.2	3.47	3.00	4.4	ac
		FHP122AL	2	10.0	11.2	3.92	3.47	4.0	ac
		FHP122AL	2	10.0	11.2	3.92	3.47	4.0	ac
		FHP122AL	2	10.0	11.2	3.96	3.46	4.1	ac
		FHP122AL	2	10.0	11.2	3.67	3.46	4.1	ac
		FHP122AL	2	10.0	11.2	3.69	3.49	4.1	ac
		FHP122AL	2	10.0	11.2	3.83	3.43	3.9	ac
		FHP122AL	2	10.0	11.2	2.96	2.85	4.9	ac
		FHP122AL	2	10.0	11.2	3.06	2.85	4.8	ac
		FHP122AL	2	10.0	11.2	3.42	3.16	4.3	ac
R2YPT140BA形	FHQ142AL	FHO142AL	1	10.0	11.2	3.14	3.19	4.1	ac
		FHP142AL	2	10.0	11.2	3.14	3.19	4.1	ac
		FHP142AL	2	10.0	11.2	3.32	3.45	4.0	ac
		FHP142AL	2	10.0	11.2	3.92	3.47	4.0	ac
		FHP142AL	2	10.0	11.2	3.92	3.47	4.0	ac
		FHP142AL	2	10.0	11.2	3.96	3.46	4.1	ac
		FHP142AL	2	10.0	11.2	3.77	3.43	4.2	ac
		FHP142AL	2	10.0	11.2	3.77	3.43	4.2	ac
		FHP142AL	2	10.0	11.2	3.83	3.43	4.1	ac
		FHP142AL	2	10.0	11.2	4.06	3.67	4.8	ac
		FHP142AL	2	10.0	11.2	4.53	3.89	4.1	ac
		FHP142AL	2	10.0	11.2	4.92	4.10	3.9	ac
R2YPT160BA形	FHQ162AL	FHO162AL	1	12.5	14.0	4.10	3.83	4.5	ac
		FHP162AL	2	12.5	14.0	3.96	2.92	4.8	ac
		FHP162AL	2	12.5	14.0	4.07	3.84	4.5	ac
		FHP162AL	2	12.5	14.0	4.28	4.02	4.7	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac
		FHP162AL	2	12.5	14.0	4.78	4.28	4.6	ac

室外ユニット	形式	室内ユニット	台数	冷房能力 (kW)	暖房能力 (kW)	冷房 消費電力 (kW)	暖房 消費電力 (kW)	省エネ率 消費効率 (APF)	区分名
R2YPT22BA形	FHQ222AL	FHO222AL	1	20.0	22.4	6.90	6.80	4.2	ac
		FHP222AL	2	20.0	22.4	6.02	6.00	4.7	ac
		FHP222AL	2	20.0	22.4	6.00	6.00	4.8	ac
		FHP222AL	2	20.0	22.4	6.92	6.80	4.0	ac
		FHP222AL	2	20.0	22.4	7.22	6.80	4.0	ac
		FHP222AL	2	20.0	22.4	6.76	6.84	3.9	ac
		FHP222AL	2	20.0	22.4	7.13	6.44	4.2	ac
		FHP222AL	2	20.0	22.4	7.24	6.44	4.2	ac
		FHP222AL	2	20.0	22.4	7.55	6.54	3.9	ac
		FHP222AL	2	20.0	22.4	7.55	6.54	3.9	ac
		FHP222AL	2	20.0	22.4	7.30	6.61	3.9	ac
		FHP222AL	2	20.0	22.4	7.45	6.64	3.9	ac
R2YPT280BA形	FHQ282AL	FHO282AL	1	25.0	28.0	9.10	8.15	3.9	ac
		FHP282AL	2	25.0	28.0	8.12	7.95	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac
		FHP282AL	2	25.0	28.0	8.40	7.70	4.5	ac

●省エネ基準について

室内ユニット	形式	冷房能力 (kW)	省エネ率 消費効率 (APF)	区分名
FHQ～形 FHP～形	上記以外	3.6	5.0	ac
		4.0	5.9	ac
		4.5	5.9	ac
		5.0	5.8	ac
		5.6	5.8	ac
		7.0	6.0	ac
		10.0	6.0	ac
		12.5	6.6	ac
		14.0	6.6	ac
		20.0	5.1	ac
		25.0	4.8	ac
		3.6	5.1	ac
上記以外	上記以外	4.0	5.0	ac
		4.5	5.0	ac
		5.0	4.9	ac
		5.6	4.9	ac
		7.1	4.8	ac
		10.0	5.1	ac
		12.5	4.8	ac
		14.0	4.7	ac
		20.0	4.3	ac
		25.0	4.0	ac
		3.6	4.0	ac

●省エネ率・消費効率 (APF) について

APFとは、JIS B 8516「2006(リニア) シェアーク」に準拠して算出される。
※R410A・R404B・2006は、JIS B 8516「2006」を適用する。(注) 日本冷凍空調工業会が作成した規格です。
・APF＝総制熱能力(能力)÷期間消費電力